



FUNKTIONSHILFZ® OF THE AGEPAN® SYSTEM:
FOR A COMFORTABLE INDOOR CLIMATE OF WELL-BEING.

All the product names and company names used in this flyer are trade names and / or registered trademarks belonging to the respective proprietors. Any reproduction requires the express permission of Sonae Arauco Deutschland GmbH and / or the respective trademark proprietor. Sonae Arauco Deutschland GmbH assumes no liability for any possible errors or omissions. The information contained in this flyer is for informational purposes only and does not constitute an offer. The information is subject to change without notice. Our detailed instructions for use must be observed. The respective building regulations must be complied with. Version: May 2022

- Pressure resistant and stable
- Quality made in Germany
- Environmentally friendly
- A one-stop solution
- Easy to work with
- For healthy living
- Weather resistant
- Fire protection
- Sound insulation

NEW!
IN PRACTICAL SIZE
1,89 m x 0,61 m

AGEPAN® UDP Inside T+G
THE PRACTICAL INTERIOR BOARD



- Pressure resistant and stable
- Quality made in Germany
- Environmentally friendly
- A one-stop solution
- Easy to work with
- For healthy living



YOUR ADVANTAGES WITH THE PLASTERABLE AGEPAN® UDP INSIDE T+G

Due to its handy format, the AGEPAN® UDP Inside T+G can be easily processed. With its diffusion-open and moisture-regulating properties, the ecological wood fibre insulation board contributes to a pleasant and healthy indoor climate.

- + Ecological AGEPAN® wood fibre insulation interior board
- + Lightweight, particularly stable and healthy for living
- + Easy handling: as a small-format board, it is ideal for the craftsman
- + Laying of flying butts
- + Can be used in drywall grid dimensions of 62.5 cm
- + Can be used on both sides, less wastage
- + Simple processing with commercially available woodworking machines
- + Extremely pressure resistant with ≥ 250 kPa
- + Lighter than commercially available interior finishing boards based on gypsum (raw density = 270 kg/m³)

AREAS OF APPLICATION

- *Wood-fibre insulation board as cladding for wood and metal support structures for non-loadbearing internal partitions, without requirements for fire protection, sound insulation and fall protection
- Roof slopes / Knee wall
- Ceilings and roof slope areas in dry constructions
- Plaster coatings with mineral and clay plaster possible



The pressure-resistant interior plaster board for mineral and clay plasters

TECHNICAL DATA

PROPERTY	UNIT	VALUE
Bulk density	kg / m ³	270
Compressive strength	kPa	≥ 250
Nominal thermal conductivity λ_0	W / (m*K)	0,051
Rated thermal conductivity λ_R	W / (m*K)	0,054
Water vapour diffusion resistance factor μ		5
Specific thermal capacity	J / (kg*K)	2100
Fire behaviour acc. to DIN EN 13501-1		E
Building material class acc. to DIN 4102		B2
Formaldehyde emission class		E1 – formaldehyde-free glued*1

*1 Meets the requirements according to the German Chemicals Prohibition Ordinance (E05)

DELIVERY PROGRAMME

Calculation dimension	mm	1890 x 610
Coverage	mm	1870 x 590
Nominal thickness	mm	25
Cover area per board	m ²	1,10
Weight per board*2	kg	7,78
Package content	Stück	42
Cover area per package	m ²	46,20
Weight per package*2	kg	326

*2 Approximate value

Use products that are certified accordingly. FSC®- and PEFC-certified products can be delivered on demand and within availabilities. Please specify when ordering.

