



AGEPAN® THD Install is a wood fibre insulation board manufactured in a dry process in accordance with DIN EN 13171. The permeable and heat-insulating board is bonded without formaldehyde and is therefore as healthy as natural wood.

We spend most of our lives indoors. Therefore, it is not surprising that the buildings we inhabit and the materials they are made of can have a significant impact on our health and well-being.

ROOF WALL

INSIDE INSULATION (



## IS EXTERNAL WALL INSULATION NOT POSSIBLE?

to access from the outside. With the AGEPAN® THD Install, the exterior wall can be easily

- of the weather



## APPLICATION AREAS

- + Installation level
- + Pressure-resistant interior insulation
- + Roof and wall

- + New construction and renovation
- + Exterior wall insulation from the inside

## RECOMMENDED BY PROFESSIONALS AND CONFIRMED BY SATISFIED BUILDERS

- + Perfect indoor climate
- + Diffusion-open construction
- + Energy cost savings
- + Protection against summer heat

- + Winter cold protection
- + Short construction times
- + Soundproofing
- + Fire protection





## THE ADVANTAGES

- + "Slim" walls increase your living space and at the same time provide optimum protection against heat and cold.
- + When used as interior insulation, the AGEPAN® THD Install provides additional protection against temperature fluctuations, making it an ideal component for an excellent indoor climate.
- + The AGEPAN® THD Install can be clad directly with gypsum plasterboards / gypsum fibreboards or plastered with approved systems, e.g. red lime from Knauf Gips KG, CLAYTEC® clay plaster or akurit lime plaster.
- + Ideal room acoustics: no muffled sound when knocking against the wall, no cavities.
- + Used in a system, the AGEPAN® THD Install optimises sound insulation in the house.
- + When used in a system, fire resistance classes up to F 90-B can be achieved.
- + Quick and uncomplicated incorporation of installation ducts.



damaging the vapour barrier. No pre-drilling necessary.

\* Chipboard screw 6 x 50 mm, the minimum distance between the screws is 10 cm.









Sonae Arauco products are glued formaldehyde-free.





FSC®- and PFFC-certified products can be delivered on demand

and within availabilities. Please specify when ordering





Pressure

resistant and

stable



FUNKTIONSH (2z°



Environmentally

friendly



solution



work with



For healthy

livina



insulation

Your AGEPAN® SYSTEM Partner

Quality made

in Germany

