



Unique thanks to its asymmetrical density profile.



Bracing or load-bearing in accordance with the general building authority approval.

IDEAL FOR PREFABRICATION AGEPAN[®] THD STATIC

AGEPAN[®] THD STATIC IS INTERESTING FOR



CARPENTRY AND TIMBER CONSTRUCTION COMPANIES WHICH

- produce one-sided planked wooden frame walls
- offer or wish to offer self-build houses
- are not externally monitored by the RAL Quality Mark for timber house building
- attach importance to short construction time, speed and yield, since the construction is already closed from the outside
- want to close timber frame walls (timber panel construction) from the inside, independent of weather conditions, with low noise levels and a high degree of safety at work



BENEFITS FOR CARPENTRY AND TIMBER CONSTRUCTION COMPANIES WHO PROCESS AGEPAN[®] THD STATIC AND INSULATE THE PARTITIONS FROM WITHIN

- wooden frame construction is protected against precipitation
- moisture is not trapped in the construction
- compartment insulation can be inserted conveniently and weather-independently from the inside after erection
- no need to install or dismantle equipment – it can be stored behind closed doors
- less noise on site, as the timber frame walls are insulated from the inside
- in the case of ventilated facades, the counter battens can be pre-assembled in the production hall
- construction debris can be picked up easily on the level surface, clean construction sites

