



AGEPAN® THD etics X

The particularly solid plaster carrier board in the ETICS.

- + Extremely high strength due to an asymmetric density profile – reduced risk of damage
- + Excellent summer heat and winter cold protection
- + Easy installation of building accessories such as mailboxes, lamps, etc.
- + ETICS approval with Knauf and akurit render systems. ETICS on external timber walls in accordance with the national approval (abZ/aBG) Z-33.47-1724
- + High abrasion resistance – fewer fibers in the plaster, saving time and materials

AGEPAN® THD etics X

Technical Data

Property	Unit	Value
Standard		DIN EN 13171
Raw density ρ	kg/m ³	~ 230
Nominal thermal conductivity λ_D	W/mK	0,047
Rated thermal conductivity λ_B	W/mK	0,049
Water vapour diffusion resistance factor μ	–	3
Compressive stress/strength	kPa	≥ 200
Tensile strength perpendicular to the plane of the board	kPa	≥ 10
Short-term water absorption	kPa s/m ²	≤ 1
Specific thermal capacity	J/kgK	2100
Maximum application temperature	°C	110
Formaldehyde emission class		E1*; NAF (< 0,03 ppm)
Fire behavior Euroclass according to DIN EN 13501-1		E
Outdoor exposure		up to 4 weeks
Board marking		WF-EN 13171-T3-CS(10/Y)200-TR10-WS1,0-MU3
Disposal		Waste wood category A2; waste code numbers (AVV): 030105, 170201

* Meets the requirements according to the German Chemicals Prohibition Ordinance (E05)
NAF = No-added formaldehyde

Building physics parameters

Property	Unit	Board thickness (mm)		
		40	60	80
Nominal value thermal resistance R_D	m ² K/W	0,85	1,25	1,70
Thermal resistance R	m ² K/W	0,80	1,20	1,60
Water vapour diffusion equivalent air layer thickness s_d	m	0,12	0,18	0,24

Application areas Field of application according to DIN 4108-10-2021-11

Roof / Ceiling



Interior ceiling insulation (underside) or roof insulation installed beneath the rafters or structural framework, including solutions such as suspended ceilings

DI-zg



Wall



External wall insulation system with render finish

WAP-zh

Insulation of timber frame construction, timber panel construction and comparable compartments

WH



Heat and cold protection



CO₂ storage



Healthy living



Meets the requirements according to the German Chemicals Prohibition Ordinance



Formaldehyde-free glued



Weather resistant



Produced in Germany



Use products that are certified accordingly: PEFC-certified products can be delivered on demand and within availabilities. Please specify when ordering.



EMISSIÕES DANS L'AIR INTÉRIEUR
A B C
* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentée en risque de toxicité par évaluation, sur une échelle de classe allant de A (0,01 kg/m³) à C (0,10 kg/m³) (norme EN 15782)

Your AGEPAN® partner

Technical Datasheet, May 2025

Product and company names in this data sheet are trade names or registered trademarks. Reproduction is only permitted with explicit permission from Sonae Arauco. Sonae Arauco assumes no liability for errors or inaccuracies. This data sheet reflects the technical status at the time of printing and applies together with additional documents from AGEPAN®. Processing instructions and building regulations must be observed. The material suitability must be checked for the intended use.



www.sonaearauco.com