

# innovus

**Decorative Products** 

# **INNOVUS DP P2** CARB2/TSCA

Decorative surfaced particleboard panel (DP) for use in dry conditions

## **DESCRIPTION** -

INNOVUS DP P2 CARB2/TSCA is a surfaced particleboard, suitable for non-structural interior applications with dry conditions. Its surface is easy to clean and scratch & stain resistant.

Our INNOVUS DP P2 CARB2/TSCA is compliant with the limit of ChemVerbotsV (E05) and the core board is certified according to the rules of the official California Air Resources Board (CARB).

In addition to technical performance INNOVUS DP panels are sustainable and environmental friendly products.

For further information on available sizes and thicknesses, please see our Offer & Service Brochure.

### **PROPERTIES**





















A TSCA TITLE VI 8 ARB 2 CERTIFIED (SUBSTRATE)

# **APPLICATIONS**

INNOVUS DP P2 CARB2/TSCA durability, design and versatility makes it a good choice for residential, public & commercial areas and healthcare applications.

As a result of their characteristics, INNOVUS DP P2 CARB2/TSCA is widely used for office and home furniture, kitchen and bath cabinets, wall paneling, store fixtures and decoration in general.











### RECOMMENDATION

INNOVUS panels must be stored in a dry/covered building, stacked on a hard, level surface and protected from direct contact with water. Expansion and contraction in wood products is directly related to moisture content and must be considered during design and construction.

Wood based panels are biodegradable and can be recycled, follow local regulation for the disposal of residues.

To clean, simply use a cloth dampened in warm water or the usual household cleaning products. Common cleaning products or disinfectants (for example alcohol-based ones) can be used, as long as they do not contain abrasive agents, acids or strongly alkaline substances. Also, bleach or detergent products that contain high levels of chlorine should be avoided.

### ALSO AVAILABLE



www.sonaearauco.com TDS.04.23.SAD.R02





# **INNOVUS DP P2 CARB2/TSCA**

Decorative surfaced particleboard panel (DP) for use in dry conditions

### **GENERAL CHARACTERISTICS** -

PROPERTY	TEST	UNIT	Т	THICKNESS RANGE (mm)		
			<15	≥15 - 20	>20	
Tolerance on thickness relative to nominal value	EN 14323	mm	± 0,3	± 0,3	± 0,5	
Tolerance on thickness within the board	EN 14323	mm	< 0,6	< 0,6	< 0,6	
Tolerance on Length and Width	EN 14323	mm	± 5	± 5	± 5	
Flatness (only for balanced surfaces)	EN 14323	mm/m	-	≤ 2	≤ 2	

### **TECHNICAL INFORMATION**

PROPERTY	TEST	UNIT	REQUIREMENTS
Resistance to scratching	EN 14323	N	≥ 1,5
Resistance to staining	EN 14323	Rating	≥ 3
Resistance to cracking	EN 14323	Rating	≥ 3
Abrasion resistance – woodgrains & fantasises	EN 14323	Class 1	IP < 50
Abrasion resistance – unicolour	EN 14323	Class 3A	IP ≥ 150
Formaldehyde emission class			E1*

<sup>\*</sup>Compliant with limit of ChemVerbotsV (E05); uses certified substrate according to CARB 2/EPA TSCA.

INNOVUS DP P2 CARB2/TSCA panels are classified according to the criteria defined by EN 14322 - Wood-based panels - Melamine faced boards for interior uses - Definition, requirements and classification.

Physical-mechanical properties differ according to the substrate used. Please check the corresponding technical data sheet for more information.

For more information regarding the technical properties check the product Declaration of Performance (DoP).

### **CERTIFICATIONS** –

### Please pay attention to certified products:



The mark of responsible forestry FSC\* C009049







 $\mathsf{FSC}^{\$}$  and  $\mathsf{PEFC}$  -certified products are available on request and availability.

### www.sonaearauco.com

#### TDS.04.23.SAD.R02



